

POSTŘIKOVAČE VYRSA



POSTŘIKOVAČ VYR-70



Technické parametry:

- postřikovač vyrobený z mosazi a nerez oceli,
- kruhový, mosazné trysky,
- úhly vodních paprsků 26° a 22°,
- postřikovač **VYR-7001** - 3/4" vnější závit,
- postřikovač **VYR-7020** - 3/4" vnitřní závit.

	5/32" 3,96 mm.		11/64" 4,36 mm.		3/16" 4,76 mm.		13/64" 5,15 mm.		7/32" 5,55 mm.		1/4" 6,35 mm.		9/32" 7,14 mm.	
Bar	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m
2,45	94,0	29,0	1.140	30,0	1.360	30,2	1.610	32,0	1.880	32,4	2.041	34,2	3.000	36,0
3,15	1.070	30,2	1.290	31,4	1.550	32,4	1.830	33,2	2.140	34,8	2.750	36,8	3.450	37,4
3,5	1.130	30,6	1.360	31,8	1.630	32,6	1.930	33,8	2.240	35,6	2.910	37,8	3.630	38,6
4,2	1.230	31,2	1.490	32,4	1.780	33,2	2.090	34,8	2.410	36,8	3.160	39,0	3.970	41,4
4,9	1.350	31,8	1.610	33,0	1.920	33,8	2.220	35,4	2.560	37,5	3.420	40,2	4.170	43,4

	5/32 x 3/32" 3,96 x 2,38 mm.		11/64 x 3/32" 4,36 x 2,38 mm.		3/16 x 1/8" 4,76 x 3,17 mm.		13/64 x 1/8" 5,15 x 3,17 mm.		7/32 x 1/8" 5,55 x 3,17 mm.		1/4 x 1/8" 6,35 x 3,17 mm.		9/32 x 1/8" 7,14 x 3,17 mm.	
Bar	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m
2,45	1.290	29,0	1.490	29,6	2.000	31,0	2.250	31,4	2.510	32,4	3.040	33,8	3.670	34,4
3,15	1.470	30,0	1.690	31,2	2.290	31,8	2.560	32,6	2.880	34,2	3.490	36,2	4.190	36,8
3,5	1.550	30,2	1.780	31,4	2.400	32,2	2.700	33,2	3.010	35,0	3.670	37,2	4.420	38,2
4,2	1.690	30,8	1.940	32,2	2.630	32,6	2.950	34,1	3.260	36,2	4.010	38,4	4.430	40,8
4,9	1.830	31,4	2.090	32,6	2.810	33,2	3.170	34,8	3.490	36,8	4.330	39,6	5.230	42,8



POSTŘIKOVAČ VYR-86



Technické parametry:

- postřikovač vyrobený z plastu delrin a nerez oceli,
- kruhový, mosazné trysky,
- 1" vnitřní závit, úhel vodního paprsku 26°,
- postřikovač **VYR-8600** – plastový úderník,
- postřikovač **VYR-8601** – mosazný úderník.

	7/32" 5,55 mm.		1/4" 6,35 mm.		9/32 " 7,14 mm.		5/16" 7,93 mm		11/32" 8,73 mm		3/8" 9,52	
Bar	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m
2,8	1.998	36,8	2.611	39,0	3.314	39,6	4.018	40,3	4.790	41,4	5.540	44,2
3,15	2.134	37,4	2.769	39,8	3.518	40,8	4.290	41,4	5.110	43,2	5.902	46,0
3,5	2.240	38,0	2.920	40,8	3.700	42,0	4.540	42,7	5.400	45,0	6.240	47,8
4,2	2.470	39,2	3.220	42,2	4.080	43,8	4.994	45,1	5.940	47,4	6.940	50,3
4,55	2.588	39,8	3.360	43,2	4.268	44,8	5.221	43,3	6.220	48,8	7.265	50,9
5,6	2.860	42,6	3.740	46,0	4.740	47,4	5.834	49,1	6.940	52,4	8.100	55,2

	7/32 x 11/64" 5,55 x 4,36 mm.		1/4 x 11/64" 6,35 x 4,36 mm.		1/4 x 3/16" 6,35 x 4,76 mm.		9/32 x 3/16" 7,14 x 4,76 mm.		9/32 x 7/32" 7,14 x 5,55 mm.		11/32 x 7/32" 8,73 x 5,55 mm.	
Bar	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m	l/hod.	Ø m
2,8	3.200	36,8	3.780	39,0	4.030	39,0	4.610	39,6	5.150	39,6	6.520	41,4
3,15	3.460	37,4	4.030	39,8	4.280	39,8	4.900	40,8	5.440	40,8	6.980	43,2
3,5	3.540	38,0	4.280	40,8	4.540	40,8	5.180	42,0	5.760	42,0	7.340	45,0
4,2	3.960	39,2	4.680	42,2	5.000	42,2	5.720	43,8	6.370	43,8	8.100	47,4
4,55	4.140	39,8	4.930	43,2	5.180	43,2	5.980	44,8	6.620	44,8	8.420	48,8
5,6	4.610	42,6	5.440	46,0	5.800	46,0	6.620	47,4	7.420	47,4	9.400	52,4

J + J závlahové systémy, s.r.o., Příčná 24, 290 01 Senice

Tel./fax: 325 652 064, 325 652 365-6, e-mail: jerabek@zavlahy-jerabek.cz, www.zavlahy-jerabek.cz