

# POSTŘIKOVAČE VYRSA



## POSTŘIKOVAČ VYR-37



### Technické parametry:

- postřikovač vyrobený z plastu delrin,
- kruhový,
- plastové trysky s bajonetovou spojkou – otočka pouze 1/4,
- postřikovač **VYR-3701** – 3/4“ vnější závit,
- postřikovač **VYR-3702** – 3/4“ vnitřní závit.

	9/64" 3,57 mm.		5/32" 3,96 mm.		11/64" 4,36 xmm.		3/16" 4,76 mm.		13/64" 5,15 mm.		7/32" 5,55 mm.	
Bars	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m
1,75	660	26,2	800	27,8	960	29,4	1.140	30	1.340	30,8	1.550	31,2
2,1	720	27	870	28,8	1.050	30	1.250	30,6	1.480	31,4	1.720	32
2,46	770	27,6	940	29,4	1.140	30,6	1.360	31,2	1.610	32	1.880	33
3,16	870	28,4	1.070	30,2	1.290	31,4	1.550	32,4	1.830	33,2	2.140	34,8
3,51	920	28,8	1.130	30,6	1.360	31,8	1.630	32,6	1.930	33,8	2.240	35,6
4,21	990	29,4	1.230	31,2	1.490	32,4	1.780	33,2	2.090	34,8	2.410	36,8

	9/64 x 3/32" 3,57 x 2,38 mm.		5/32 x 3/32" 3,96 x 2,38 mm.		11/64 x 3/32" 4,36 x 2,38 mm.		3/16 x 1/8" 4,76 x 3,17 mm.		13/64" x 1/8" 5,15 x 3,17 mm.		7/32 x 1/8" 5,55 x 3,17 mm.	
Bars	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m
1,75	920	26	1.100	27,6	1.250	29	1.680	29,4	1.880	30,2	2.100	30,6
2,1	1.000	26,6	1.200	28,4	1.380	29,6	1.850	30	2.080	30,8	2.320	31,4
2,46	1.090	27,2	1.300	29	1.490	30,2	2.000	30,6	2.260	31,4	2.520	32,4
3,16	1.250	28,2	1.470	30	1.690	31,2	2.290	31,8	2.570	32,6	2.880	34,2
3,51	1.330	28,4	1.550	30,2	1.790	31,4	2.410	32	2.700	33,2	3.020	35
4,21	1.440	29	1.700	30,8	1.950	32	2.630	32,6	2.950	34,2	3.270	36,2



## POSTŘIKOVAČ VYR-4600



### Technické parametry:

- postřikovač vyrobený z plastu delrin,
- kruhový,
- nízký úhel vodního paprsku 7°,
- jedna nebo dvě mosazné trysky,
- 3/4“ vnější závit.

	7/64" 2,8 mm.		1/8" 3,2 mm.		9/64" 3,6 mm.		5/32" 4 mm.		11/64" 4,4 mm.		3/16" 4,8 mm.		13/64" 5,15 mm.		7/32" 5,5 mm.		15/64" 6 mm.		1/4" 6,35 mm.		17/64" 6,75 mm.	
Bars	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m	Lit./h.	Ø m
1,0	310		400	23,0	510	23,0																
1,5	380	23,0	500	25,0	620	25,0																
2,0	440	24,0	560	26,0	710	26,5																
2,5	480	25,5	630	26,5	780	27,5	950	23,0	1140	23,0	1360	24,0	1610	24,5	1880	25,0	2150	26,0	2450	26,0	2750	27,0
3,0	520	26,0	680	27,5	850	28,0	1050	24,5	1300	25,0	1530	25,5	1800	26,0	2090	27,5	2400	27,0	2700	27,5	3020	28,0
3,5	550	27,00	720	28,0	920	28,5	1140	26,0	1360	26,0	1650	26,5	1940	27,0	2250	28,0	2570	28,0	2950	28,5	3300	29,5
4,0		28,00					1200		1470	27,0	1750	27,5	50	28,0	2400	28,5	2750	29,0	3150	30,0	3520	30,5

J + J závlahové systémy, s.r.o., Příčná 24, 290 01 Senice

Tel./fax: 325 652 064, 325 652 365-6, e-mail: jerabek@zavlahy-jerabek.cz, www.zavlahy-jerabek.cz