

POSTŘIKOVAČE VYRSA



POSTŘIKOVAČ VYR-8004



Technické parametry:

- postřikovač vyrobený z mosazi,
- kruhový nebo výsečový postřikovač,
- možnost regulace dostřiku a rozptylu vodního paprsku,
- 1/2" vnější závit.

	3 mm.		3,5 mm.		4 mm.	
Bar	Lit./h.	ø m	Lit./h.	ø m	Lit./h.	ø m
1,5	450	20	580	21	730	22
2,0	510	21	660	22	850	23
2,5	550	22	740	23	950	24
3,0	630	23	810	23	1030	24
3,5	680	23	870	24	1110	25
4,0	720	24	930	25	1180	26



POSTŘIKOVAČ VYR-65



Technické parametry:

- postřikovač vyrobený z mosazi,
- kruhový nebo výsečový postřikovač,
- dvě trysky,
- postřikovač **VYR-6500** – 1" vnitřní závit,
- postřikovač **VYR-6501** – 1" vnější závit.

	7/32" = 5,55 mm		1/4" = 6,35 mm		9/32" = 7,14 mm		11/32" = 8,73 mm		3/8" = 9,52 mm	
Bar	Lit./h.	ø m	Lit./h.	ø m	Lit./h.	ø m	Lit./h.	ø m	Lit./h.	ø m
3,50	2240	33,00	2920	34,20	3700	36,00	5400	39,00	6240	40,20
4,20	2470	34,80	3220	34,80	4080	39,00	5940	40,40	6940	43,80
4,90	2670	36,00	3490	37,80	4220	42,00	6460	43,20	7530	45,00
5,25	2760	37,20	3630	38,40	4600	42,60	6710	44,40	7830	45,60
5,60	2860	37,80	3740	39,00	4740	43,20	6940	45,60	8100	46,10

	3/16" x 1/8"		7/32" x 1/8"		1/4" x 1/8"		9/32" x 1/8"		5/18" x 1/8"		11/32" x 1/8"	
	4,76 x 3,17 mm		5,55 x 3,17 mm.		6,35 x 3,17 mm.		7,14 x 3,17 mm		7,93 x 3,17 mm		8,73 x 3,17 mm	
Bar	Lit./h.	ø m	Lit./h.	ø m	Lit./h.	ø m	Lit./h.	ø m	Lit./h.	ø m	Lit./h.	ø m
3,50	2439	30,50	3020	33,60	3701	34,80	4472	36,60	5316	38,40	6086	39,6
4,20	2657	32,00	3315	35,40	4154	35,40	4927	39,60	5770	40,80	6744	42
4,90	2747	32,00	3474	36,00	4246	37,80	5064	40,80	6040	42,00	7040	42,6
5,25	2975	32,30	3769	37,80	4542	39,00	5495	43,20	6517	44,50	7585	45,1
5,60	3133	33,00	3928	38,40	4723	39,60	5632	43,80	6722	45,80	7834	46,3

J + J závlahové systémy, s.r.o., Příčná 24, 290 01 Senice

Tel./fax: 325 652 064, 325 652 365-6, e-mail: jerabek@zavlahy-jerabek.cz, www.zavlahy-jerabek.cz